

BTP-M280A


Impact Receipt Printer



Preferred for POS, Bar & Kitchen Printer Applications

The BTP-M280A produces either receipts or kitchen orders faster than other popular impact printers. Featuring trouble-free drop-and-print paper loading, it is adjustable to accommodate 76, 70, or 58mm paper rolls. Print is clear and precise, allowing you to print long-lasting receipts with coupons, rebates and specials.

- Auto-Cutter and Paper Take-Up
- Serial, Parallel, Ethernet and Wireless WiFi Interface Options
- Two Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Extraordinary Reliability
- Contains Everything Necessary in the Carton – Including Communications Cables



BTP-M280A Impact Receipt Printer



Drop and Print Paper Loading with Built-In Paper Width Selector



Built-In Wall Mount Capability and Optional Audio/Visual Print Messenger



Conceal the Power Supply in the Optional Power Supply Cover



Includes Everything Necessary in the Carton

Features

Proven impact printing technology preferred for POS kitchen printer applications.

- Everything You Need is in the Carton
- Serial, Parallel, Ethernet and Wireless WiFi Interface Boards Available
- Uses the Same Interface Boards as Other SNBC Printers
- Auto-Cutter with Selectable Full or Partial Cut
- Two-Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Fast 4.7 Lines per Second Print Speed
- Drop and Print Paper Loading
- Built-In Wall Mount Capability
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches
- Includes Starter Paper Roll, Paper Width Selector, Appropriate Communications Cable, Power Adapter and Cord, Ribbon, CD-ROM with Drivers, Utilities and User's Manual

Optional Devices / Upgrades

Upgrade your printer with these easy-to-add options:

- Serial, Parallel, Ethernet and Wireless WiFi Interface Boards Are User Interchangeable
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed
- Power Supply Cover

Ports and Connectivity

A Choice of Serial (Shown), Parallel, Ethernet or Wireless WiFi Interface Boards Available

B Cash Drawer

C DC 24V Power-In

Specifications

Max. Print Speed:	4.7 Lines per Second / 19.6mm per Second
Printing Method:	Impact
Characters Per Line – Font A:	33 / 35
Font B:	40 / 42
Characters Size – Font A:	9 x 9
Font B:	7 x 9
Paper Roll Type – Width:	76 / 69.5 / 57.5mm ± 0.5mm
Maximum Diameter:	83mm
Paper Thickness:	0.06mm ~ 0.085mm
Auto Paper Cutting Method:	Auto-Cutter with Selectable Full or Partial Cut
Inking Supply:	ERC-38 Ribbon Cartridge (Black/Red)
Reliability – MTBF:	180,000 Hours
MCBF:	18,000,000 Lines
Printhead Life:	150,000,000 Characters
Cutter Life:	1,500,000 Cuts
Character Set – Alphanumeric:	95
International:	13
Graphic:	128 x 8 Page
Interpreter:	ESC/POS™
Interface:	Serial / Parallel / Ethernet / Wireless WiFi
Drivers – 32-bit:	Windows XP Professional / XP Home Edition / 2000 Server / 2000 Professional
64-bit:	Windows Server 2012 / Windows XP
32 and 64-bit:	Windows 10 / Windows 8 / Windows 7 / Server 2008 / Server 2003 / Vista
Other:	Linux / OPOS / BYJavaPOS Windows / BYJavaPOS Linux
Software Development Kit:	iOS / Android
Drawer Port:	2 Port (+24VDC) with Drawer Compulsion
Data Buffer– Rec. Buffer RAM:	4 KB RAM
RAM Bitmap:	8 KB
Flash Bitmap:	128 KB
Power Supply:	AC 100 ~ 240 V, 50/60 Hz Adapter Included
Current/Power Usage:	1.5A / 36W
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)
Operating Humidity:	20% ~ 90% RH (Non-Condensing)
Dimensions / Weight – Unit:	6-5/16"W x 11-3/4"D x 6-5/8"H
Shipping Carton:	14"L x 9"W x 11"H / 10 lbs.
Safety and EMI:	FCC / RoHS

